



**Rinnai**  
R98i/R98e

## TANKLESS WATER HEATERS MODEL SERIES R98 (3237FFU/W)

### FOR RESIDENTIAL APPLICATIONS

### THE ALL NEW HIGH OUTPUT WATER HEATER

Need more power and output? The Rinnai R98 offers our highest maximum output of 9.8 gallons per minute at 237,000 BTUs. With 15-27% more capacity than our R85 series, the R98 is the perfect solution for custom luxury homes with spa tubs, body sprays, and other high-end hot water demands. Whether alone or in combination with multiple units, the R98 is your high output source for endless hot water!



### ENHANCED FEATURES — ENHANCED PERFORMANCE

The new high-output unit is a perfect fit for large-sized residential homes

- Hot water capacity of 0.9 - to 9.8 GPM (at a 35° F rise); 19,000 - 237,000 BTUs
- Packaged with a Rinnai MC-91 controller
- Internal or external installations

### NEVER RUN OUT OF HOT WATER

- Endless hot water
- Heats water at a consistent temperature
- Delivers hot water to multiple water sources simultaneously at a constant user-set temperature

### SAVE MONEY ON ENERGY COSTS

- Water is heated only as needed when hot water demand is detected

Temperature Rise (°F)	GALLONS PER MINUTE			
	R85i (1 unit)	R98i/e (1 unit)	R85i (2 units)	R98i/e (2 units)
75	4.2	5.3	8.4	10.6
60	5.2	6.6	10.4	13.2
45	7.0	8.8	14.0	17.6
35	8.5	9.8	17.0	19.6



R98i Model Series  
Shown With  
Integrated Control

## MORE POWER - MORE CAPACITY

### THE RINNAI ADVANTAGE GUARANTEE

- No tank - reducing ruptures and bacteria buildup
- Exceptional Warranty - 10 years limited on heat exchanger, 5 years on all other parts, 1 year for labor
- Scald-resistant with use of digital temperature control

### OPTIMIZE VALUABLE SPACE

- Frees up valuable living space
- Can be strategically mounted on an interior wall or exterior wall without the need for additional venting

### VENTING CONSIDERATIONS

- Requires separate 4" vents for intake and exhaust due to high BTU output.

### MODEL R98i



### THE R98 MODELS INCLUDE THE FOLLOWING



#### MC-91 CONTROLLER

Digital control pad to operate at exact user-specified temperatures.

- Integrated into the internal unit
- Included as a remote controller for the external unit

MODEL SERIES	R98i / R98e
Dimensions (Water Heater Unit)	9.1" D x 18.5" W x 23.6" H
Weight	55 lbs.
Maximum/Minimum Gas Rate (Input BTUs)	237,000 BTU / 19,000 BTU
Thermal Efficiency (R98i Model Series)	Natural Gas: 84%    Propane: 85%
Thermal Efficiency (R98e Model Series)	Natural Gas: 85%    Propane: 83%
Hot Water Capacity Range	0.9 to 9.8 GPM
Maximum Hot Water Capacity (35°F Rise)	9.8 GPM (588 GPH)
Setpoint Temperature (Without Remote)	Factory Setting - 120°F
Temperature Range with Remote Key Pad(s) Connected	MC-91-1: 98° - 140° F

Rinnai is continually updating and improving products; therefore, specifications are subject to change without prior notice. Local, state, provincial and federal codes must be adhered to prior to installation.

### CONTACT YOUR LOCAL AUTHORIZED DEALER

### Rinnai Corporation

103 International Drive  
Peachtree City, GA 30269

**Toll Free 1-800-621-9419**

Phone: 678-829-1700

Fax: 678-364-8643

Visit Our Web sites [www.rinnai.us](http://www.rinnai.us) • [www.foreverhotwater.com](http://www.foreverhotwater.com)

E-mail: [marketing@rinnai.us](mailto:marketing@rinnai.us)

# Rinnai®

